

## TECHNICIAN'S INSTRUCTIONS

### AOM - 224: Spot / Rapid Repair on a Clear over Base Finish

#### Your objective:

- To match and mix vehicle colours to the correct shade.
- To demonstrate the application of topcoats.
- To demonstrate blending and fading techniques.
- To demonstrate how to rectify minor surface defects by using, sanding and polishing techniques.

#### Facilities, equipment and materials that you must check are to hand at the workstation prior to the assessment:

- Personal Protective Equipment (PPE)
- Vehicle protection equipment and materials
- Technical and safety information for the products
- Relevant tinters, basecoats and clearcoats
- A suitable vehicle panel which will be used for application
- A suitable vehicle or panel for colour matching (with the colour code or reference available)
- Rubbing compound, polish and cloth
- Colour retrieval system
- Colour matching equipment
- Cleaning agents and dispensers
- Cleaning paper/cloth
- Masking materials and dispensers
- Mixing scheme and scales
- Paint consumables, for example: thinners, hardeners tack cloths, mixing pots, paint strainers, disposable paint pots, additives and blending / fade out products.
- Spray guns
- Spray gun cleaning equipment
- Paint test cards and /or panels
- Drying and curing equipment
- Abrasives for fault rectification / dirt inclusions
- Polishing equipment

#### Complete the following tasks:

1. Set up and wear the appropriate personal protective equipment.
2. Consult relevant technical information and ensure that ADAS systems are not affected by the refinishing processes.
3. Identify the foundation and substrate material.
4. Identify the colour and shade of the vehicle or panel.
5. Prepare and mix the paints and clearcoats as stated by the paint manufacturer.
6. Select and use additives where applicable.
7. Set up, adjust and test the spraying equipment.
8. Apply the colour variants to spray out cards or a test panel.



9. Identify the spray out card which matches the vehicle or panel.
10. Blend the colour to adjacent areas, using the paint manufacturer's guidelines.
11. Mix the clearcoat as stated by the paint manufacturer.
12. Apply and fade out the clearcoat in accordance with the paint manufacturers guidelines.
13. Check the newly apply coatings for evenness and any surface defects.
14. Cure the applied coatings as stated by the paint manufacturer.
15. Rectify minor surface defects, for example dirt inclusions.
16. Dispose of waste materials safely and legally.
17. Clean all the equipment.
18. Return and store the tools, equipment, products and consumables in their appropriate place.

**Time limit – 2.0 hours (Excluding any drying or curing times)**

DRAFT

## WORKSTATION REQUIREMENTS

### AOM - 224: Spot / Rapid Repair on a Clear over Base Finish

#### Facilities, equipment and materials required at the workstation:

- Personal Protective Equipment (PPE)
- Vehicle protection equipment and materials
- Technical and safety information for the products
- Relevant tinters, basecoats and clearcoats
- A suitable vehicle panel which will be used for application
- A suitable vehicle or panel for colour matching (with the colour code or reference available)
- Rubbing compound, polish and cloth
- Colour retrieval system
- Colour matching equipment
- Cleaning agents and dispensers
- Cleaning paper/cloth
- Masking materials and dispensers
- Mixing scheme and scales
- Paint consumables, for example: thinners, hardeners tack cloths, mixing pots, paint strainers, disposable paint pots, additives and blending / fade out products.
- Spray guns
- Spray gun cleaning equipment
- Paint test cards and /or panels
- Drying and curing equipment
- Abrasives for fault rectification / dirt inclusions
- Polishing equipment

#### Workstation set up required:

- Provide all the tools, equipment, products and consumables which are appropriate for this task.

**Note:** All Material Safety Data Sheets and Technical Data Sheets must be available

- Provide the personal protection equipment in conjunction with the *Material Safety Data Sheets*.
- Provide vehicle protection equipment - any dispensers must be working efficiently.
- Provide cleaning and static removal equipment.
- Supply a previously painted vehicle panel which has been prepared to accept a spot / rapid repair. **Note:** This panel can be the same one which has been used throughout the paint accreditation assessment.
- Provide a colour code or reference to enable the candidate to select the correct shade.
- Provide colour matching and colour retrieval equipment.
- Supply mixing and measuring equipment which is suitable for the task.
- Provide the equipment to carry out a viscosity check.
- Provide spray guns which contain the set ups for the products used within this task
- Provide equipment which is suitable to dry and cure the coatings used in this task.
- Supply tools and equipment to rectify paint surface defects, such as dirt inclusions.



- Provide paint spraying equipment which is appropriate for this task.
- Provide equipment to dry and cure the paints and clearcoat.
- Provide spray gun cleaning equipment which is appropriate for the products used.
- Supply the appropriate disposal bins for different types of contaminated waste.
- Check and ensure the work areas are clean and free from contaminants.

DRAFT



ASSESSMENT RESULTS SHEET

AOM - 224: Spot / Rapid Repair on a Clear over Base Finish

Technician's Name:

Registration Number:

Assessor's Name:

Date: / /

Start time:

Completion time:

Critical competences <b>The candidate:</b>	Achieved
Set up and wore the appropriate personal protective equipment.	
Comments:	
Consulted relevant technical information and ensure that ADAS systems are <b>not</b> affected by the refinishing processes.	
Comments:	
Identified the foundation and substrate material.	
Comments:	
Identified the correct colour and shade of the vehicle or panel.	
Comments:	
Prepared and mixed the paint and clearcoats as stated by the paint manufacturer.	
Comments:	
Selected and used additives where applicable.	
Comments:	
Set up, adjusted and tested the spraying equipment.	
Comments:	
Applied the colour variants and clearcoat to a spray out card or a test panel.	
Comments:	
Identified the spray out card which matched the vehicle or panel.	
Comments:	
Blended the colour to adjacent areas, using the paint manufacturer's guidelines.	



Comments:	
Mixed the clearcoat as stated by the paint manufacturer.	
Comments:	
Applied and faded out the clearcoat in accordance with the paint manufacturer's guidelines.	
Comments:	
Checked the newly applied coatings for evenness and any surface defects.	
Comments:	
Cured the applied coatings as stated by the paint manufacturer.	
Comments:	
Rectified any minor surface defects, for example dirt inclusions.	
Comments:	
Disposed of waste materials safely and legally.	
Comments:	
Cleaned all the equipment.	
Comments:	
Returned and stored the tools, equipment, products and consumables in their appropriate place.	
Comments:	
Worked safely, obeying safe working practices throughout the assessment.	
Comments:	
Cleaned and left the work area safe on completion of the tasks.	
Comments:	
Completed the task in the allocated time (2.0 hours).	
Comments:	



Assessor comments:

Assessor's signature:

PASS / REFERRED

Assessor's PIN:

DRAFT